



Fabriksvangen 15 3550 Slangerup - Tlf. +45 48 10 33 00 - Mail: salg.slangerup@iq-products.com

HOSE CLAMP W2 9MM

W2 Endless wormdrive hose clamps feature a 9 mm stainless steel band (AISI 430) and stainless-steel housing (AISI 430). The stainless-steel screw is galvanized bichromate. At fitting, this hose clamp require ≥ 3 Nm of torque.



CLAMPING RANGE MIN/MAX MM	ITEM NO.	TORQUE AT BREAK Nm	PIECES IN BOX Pcs.
8-12	9280930081200	≥ 5	50
10-16	9280930101600	≥ 5	50
12-20	9280930122000	≥ 5	50
16-25	9280930162500	≥ 5	50
20-32	9280930203200	≥ 5	50
25-40	9280930254000	$\geq 5,5$	50
32-50	9280930325000	$\geq 5,5$	50
40-60	9280930406000	$\geq 5,5$	50
50-70	9280930507000	$\geq 5,5$	50
60-80	9280930608000	$\geq 5,5$	50
70-90	9280930709000	$\geq 5,5$	50
80-90	9280930809000	$\geq 5,5$	10
90-110	9280930901000	$\geq 5,5$	10

CLAMPING RANGE MIN/MAX MM	ITEM NO.	TORQUE AT BREAK Nm	PIECES IN BOX Pcs.
100-120	9280931002000	$\geq 5,5$	10
110-130	9280931103000	$\geq 5,5$	10
120-140	9280931204000	$\geq 5,5$	10
130-150	9280931305000	$\geq 5,5$	10
140-160	9280931406000	$\geq 5,5$	10
150-170	9280931507000	$\geq 5,5$	10
160-180	9280931608000	$\geq 5,5$	10
170-190	9280931709000	$\geq 5,5$	10
180-200	9280931800000	$\geq 5,5$	10
190-210	9280931901000	$\geq 5,5$	10
200-220	9280932002000	$\geq 5,5$	10
210-230	9280932103000	$\geq 5,5$	10

- All technical specifications apply to a temperature of $23^{\circ} \text{C} \pm 2^{\circ} \text{C}$ (ISO 291)
- The tolerance on all specifications $\pm 5\%$ (Tolerance Percentage is applicable on ALL DATA across our range)
- To verify if the item of your interest is "on stock" or "on demand" please contact us.