Fabriksvangen 15 3550 Slangerup - Tlf. +45 48 10 33 00 - Mail: salg.slangerup@iq-products.com

PROPANE HOSE

Flexible, smooth, orange hose for liquefied petroleum gas (LPG), propane/butane, compliant with EN ISO 3821. The hose is primarily designed for industrial welding and cutting applications, meeting the latest standards of EN ISO 3821 and EN 559, ensuring high performance and reliability under demanding conditions.

Material:

Lining: NBR Rubber, Black smooth

Reinforcement: PVA

Cover: EPDM, Orange smooth

Temperature range:

- -30°C – +80°C

Inner Diameter Inch / MM	**Outer Diameter** MM	**Working Pressure** Bar / PSI	**Burst Pressure** Bar / PSI	**Wall Thickness** MM	**Weight** g/MT	**Bending Radius** MM	**Item Number**	**Coil length** MT	**EAN-number**
¼" / 6,3	13,30	20 / 290	60 / 870	7,00	141	40	IQ2820-006	50	5 714397 000882
5/16" / 8	15,00	20 / 290	60 / 870	7,00	173	40	IQ2820-008	50	5 714397 014278
3/8" / 10	17,00	20 / 290	60 / 870	7,00	203	50	IQ2820-010	50	5 714397 000950

** All technical specifications apply to a temperature of 23° C ± 2° C*