



Fabriksvngen 15 3550 Slangerup - Tlf. +45 48 10 33 00 - Mail: salg.slangerup@iq-products.com

K-VLDR CAM & GROOVE TYPE D

CAM & GROOVE Stainless Steel Internal Thread:

Quick-connect coupling featuring a female adapter and internal thread, designed for efficient fluid transfer. Made from durable stainless steel, it offers excellent corrosion resistance and high strength.

Temperature range:

➤ -20°C – +120°C



Inch	½" – 2"	2 ½"	3"	4"	5"	6"	8"
Scale	Bar / Psi	Bar / Psi	Bar / Psi	Bar / Psi	Bar / Psi	Bar / Psi	Bar / Psi
Working Pressure	18 / 250	11 / 150	9 / 125	7 / 100	5 / 75	5 / 75	3 / 50

Type	Material	Description	Item Number	EAN-number
Type D	Stainless Steel	CAM & GROOVE TYPE D SS D. 1/2"	K-VLDR013A	5 714397 006655
Type D	Stainless Steel	CAM & GROOVE TYPE D SS D. 3/4"	K-VLDR019A	5 714397 006730
Type D	Stainless Steel	CAM & GROOVE TYPE D SS D. 1"	K-VLDR025A	5 714397 006815
Type D	Stainless Steel	CAM & GROOVE TYPE D SS D. 1-1/4"	K-VLDR032A	5 714397 006891
Type D	Stainless Steel	CAM & GROOVE TYPE D SS D. 1-1/2"	K-VLDR038A	5 714397 006976
Type D	Stainless Steel	CAM & GROOVE TYPE D SS D. 2"	K-VLDR050A	5 714397 007041
Type D	Stainless Steel	CAM & GROOVE TYPE D SS D. 2-1/2"	K-VLDR063A	5 714397 007102
Type D	Stainless Steel	CAM & GROOVE TYPE D SS D. 3"	K-VLDR075A	5 714397 007188
Type D	Stainless Steel	CAM & GROOVE TYPE D SS D. 4"	K-VLDR100A	5 714397 007263
Type D	Stainless Steel	CAM & GROOVE TYPE D SS D. 6"	K-VLDR150A	5 714397 007355
Type D	Stainless Steel	CAM & GROOVE TYPE D SS D. 8"	K-VLDR200A	5 714397 007393

* All technical specifications apply to a temperature of 23° C ± 2° C