Fabriksvangen 15 3550 Slangerup - Tlf. +45 48 10 33 00 - Mail: salg.slangerup@iq-products.com

EXHAUST HOSE

General Exhaust & Hot Gas Hose

A lightweight and crush-resistant hose designed for the extraction of vehicle exhaust and other warm gases. Ideal for use on floors, winders, and suspended systems in garages, workshops, and testing facilities. Built with durable polyamide spirals for enhanced flexibility and resilience.

Material:

Lining: Rubber Coated Fabric with Black **EPDM**

Reinforcement: Spiral in **EPDM** rubber-coated polyamide.

Temperature range:

- -40°C – +170°C

Inner Diameter Inch / MM	**Bending Radius** MM	**Weight** g/MT	**Item Number**	**Coil length** MT
2” / 51	70	540	TG6510-051	20
2-1/2” / 63	80	580	TG6510-063	20
3” / 76	95	830	TG6510-076	20
- / 80	100	870	TG6510-080	20
- / 90	105	930	TG6510-090	20
4” / 102	110	980	TG6510-102	20
5” / 127	130	1.300	TG6510-127	20
6” / 152	140	1.580	TG6510-152	20
8” / 203	185	2.080	TG6510-203	20

** All technical specifications apply to a temperature of 23° C ± 2° C*